

INFORMA

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

S-E-C-R-E-T

COUNTRY Yugoslavia/USSR

REPORT

25X1

SUBJECT Soviet Manufactured Radio Receiver
Used by the Yugoslav Army

DATE DISTR. 31 January 1958

NO. PAGES 1

REQUIREMENT
NO.

RD PROCESSING COPY

REFERENCES

25X1

DATE OF
INFO.PLACE
ACQUIRED

25X1

SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL OF CONTENT IS TENTATIVE.

three-page report

concerning a Soviet-manufactured radio receiver used by

the Yugoslav Army

25X1

25X1

REFERENCE COPY

S-E-C-R-E-T

STATE	ARMY	X	NAVY	AIR	FBI	AEC						
-------	------	---	------	-----	-----	-----	--	--	--	--	--	--

(Note: Washington distribution indicated by "X"; Field distribution by "#")

25X1

INFORMATION REPORT INFORMATION REPORT

SECRET

ATTACHMENT

ATTACHME

25X1

During September 1956 the Yugoslavs received, from the Soviets about one hundred military radio receivers intended for stationary or mobile employment by the ground forces. The receivers [REDACTED]. Their characteristics and use resemble those of the US model BC 312/342.

25X1

The range of the receiver is from 1.5 to 21 megacycles in six bands and it is equipped with Soviet tubes. It differs from the US type inasmuch as it may be fed with a 12-volt current, either alternating or direct, with a rotating converter and can therefore be used as a stationary or mobile set.

The receiver is equipped with a device which varies the width of the band in steps of 0.5 to 3.5 kilocycles continuously; the device, although of the piezoelectric crystal variety, is much more flexible than those with normal crystal filters so that it can be used by untrained operators, appreciably increasing communications sureness when the signal is difficult to hear because of interference.

SECRET

25X1

The filter ~~has no drift~~ has the virtue of preventing the signal from drifting or detuning; further, the two standard selectivity and phasing controls are inexistent (as in the Super Pro, or SX 28, or AR 88); there is only one control, that is, width of the individual band.

The device is drawn in the attached sketch and has two identical filters in stages, tuned on 470 kilocycles and furnished with two quartzes, Q1 and Q2. Note that each filter, in addition to its Q crystal, has two resonant circuits, one input and one putput. The two resonant circuits in each filter are tuned by a small-capacity variable condenser having rotors which are offset 180 degrees, so that while the capacity of one condenser increases, that of the other decreases. Thus, acting on the variable, the input of the first filter is tuned toward minor frequencies and the output circuit is detuned toward major frequencies, and similarly for the circuits of the second filter.

In this manner the response curve of the filter appears symmetrical on its sides and the response inside the individual band is more uniform. Obviously, with narrow band conditions the resonant circuits are detuned--as we saw in a symmetrical way--with respect to the frequency of the crystal. With wide band conditions, the circuits are tuned on the crystal frequency, with consequent increase of the series impedance and decrease of selectivity.

The multiple effect of the response of the staged filters, and the staggered adjustment of the various resonant circuits give the response inside the individual band a flat top shape, contrary to what happens in normal crystal filters, even under conditions of minimum selectivity. The parallel capacitance of the crystals is exactly neutralized by trimmers CN_1 and CN_2 , which contributes to the maximum steepness of response on one of its sides, the steepness on the other side being less but always great.

SECRET

25X1

Measurements taken demonstrate that under wide band conditions (3.5 kilocycles at 3 decibels) the response falls ~~within~~ 60 decibels at one kilocycle from the end of the band, whereas under narrow band conditions ~~it is 2 kilocycles at 40 decibels~~ (that is, 500 cycles at 3 decibels) the width is 2 kilocycles at 40 decibels.

SECRET

25X1

Sanitized Copy Approved for Release 2010/06/25 : CIA-RDP80T00246A039900180001-0
25X1

Page Denied

Sanitized Copy Approved for Release 2010/06/25 : CIA-RDP80T00246A039900180001-0